

## Aquarella2 Paper 210

— matt 3338 - 210 g/m<sup>2</sup>

Premium matt art paper with a high quality aquarelle effect and a slight structure for demanding art reproductions, portraits, and much more.



The mark of  
responsible forestry

### Applications

- High quality photo reproduction
- Framed art

### Advantages

- Matt effect with a slightly textured surface
- Water-resistant
- Instant dry
- Excellent colour rendering
- Natural white paper similar to traditional art paper
- Acid-free
- With no optical brightener

**Aquarella2 Paper 210****— matt 3338 - 210 g/m<sup>2</sup>****List of Printers**

<b>Printer</b>	<b>Ink</b>	<b>Quality</b>
Hewlett Packard DesignJet Z 2100 Vivera Pigment	Inkjet with pigment	Excellent
Hewlett Packard DesignJet Z 3100 Vivera Pigment	Inkjet with pigment	Excellent
Hewlett Packard DesignJet Z 6100 / 6200 / 6600 / 6800	HP Vivera/Vivid Photo ink	Excellent
Epson Stylus Pro 7600 / 9600 UltraChrome™	Inkjet with pigment	Excellent
Epson Stylus Pro 4800 UltraChrome K3	Inkjet with pigment	Excellent
Epson Stylus Pro 4880 / 7880/ 9880 / 11880 UltraChrome K3 Vivid Magenta	Inkjet with pigment	Excellent
Mutoh Valuejet 1304W / 1304WU / 1604WU / 1638W	Inkjet with pigment	Excellent
Canon iPF 5000 / 8000 / 9000	Inkjet with pigment	Excellent
Epson Stylus Pro 10000 CF ColorFast™-ink	Inkjet with pigment	Good
Epson Stylus Pro 7000 / 9000	Inkjet with Dye	Good
Epson Stylus Pro 7500 / 9500 ColorFast ink	Inkjet with pigment	Good
Epson Stylus Pro 4000-C8 UltraChrome ink	Inkjet with pigment	Good
Canon W 6200 / 8200 pigmented ink	Inkjet with pigment	Good
Canon W 6400 / 8400 pigmented ink	Inkjet with pigment	Good
Hewlett Packard DJ 5000 (PS) / 5500 (PS)	Inkjet with Dye	Fair
Hewlett Packard DJ 5000 (PS)/ 5500(PS) UV+	Inkjet with pigment	Fair
Océ Display Graphics Systems / Rastergraphics Arizona 500	Inkjet with Solvent Ink	Fair

Last update: 02.10.2015

**Aquarella2 Paper 210****— matt 3338 - 210 g/m<sup>2</sup>****Physical Properties**

Weight (Total) [gsm]	210	ISO 536
Thickness (total) [microns]	285	ISO 534
Whiteness (CIE, D65) [%]	75	ISO 11475
Chromaticity (D65 / 10°)	L* 97.0, a* 0.0 b* 3.4	DIN 6174
Opacity [%]	> 95	ISO 2471

**General tips & storage**

To maintain the quality, paper should be stored and converted under conditions of 30-65% relative humidity and at temperatures of 10-30 °C.

The values provided on this datasheet are only for orientation.

Before using our media please check its compatibility for your printer and intended application. Technical specifications are subject to change, therefore we do not take responsibility for any misprints resulting from technically modified inks and/or printers.